

Fig. 1




Fig. 2

DATA

FIG. 3

OOSUSSY SULPROP

	1	2	3	4	_5	6	7	8	9	10	12	13	14	15	16	17	18	19	20	22	23	24	25	26	27	28	29	30	31
16-BIT SOURCE PORT NUMBER <u>80</u> 16-BIT DES									ES1	INA	ATION PORT NUMBER 82																		
											32	-BIT	SE	QUE	NC	E NI	JME	ER											
L						_				32-	BIT	ACK	NO	WLE	DG	MEN	IT N	UМ	BEF	₹									
L	IDR	LGT	Н		RES	SER	VEC)	U	Α	Р	R	S	F					-	6-B	IT W	VINC	ow	SIZ	E			_	
				16	S-BIT	ТС	PC	HEC	KSI	JM			•						16-	BIT	UR	GEN	T P	NIC	ΓER				
7													PTI	ONS	(IF	AN'	Y)							_					
7													DA	TA (IF A	NY)						-							

Fig. 4




Fig. 5




Fig. 6




Fig. 7

150	152	154	156				
CLIENT IP ADDRESS	CLIENT PORT	DESTINATION IP ADDRESS	DESTINATION PORT				
1.2.3.4	544	20.21.22.23	80				
5.6.7.8	1039	24.25.26.27	80				
9.10.11.12	100	28.29.30.31	80				
13.14.15.16	1087	32.33.34.35	80				

Fig. 8




Fig. 9




Fig. 10




Fig. 11

COLONIA TONDO




Fig. 12




Fig. 13




Fig. 15




Fig. 16